PREMIUM LOCKERS FOR SECURE STORAGE OF TENANTS' PERSONAL ITEMS

▶ **EASY INSTALL**
Component panels are pre-punched and slotted for easy assembly and relocation using standard hand tools. Units can either be bolted to the floor or to the wall.

▶ **FLEXIBLE CONFIGURATION**
Lockers are available in single-, double- and triple-tier configurations, and can also be combined to fit your needs.

▶ **CAD SUPPORT**
We can support you with CAD drawings to show where our lockers can be located within your space.

Stor-More® Framed Welded Wire Tenant Storage Lockers provide sturdy and secure storage with a sleek design. Their heavy-duty construction and powder coated finish ensure years of maintenance-free performance.

The modular design of these lockers, along with their pre-punched and slotted panels, allows for easy planning, installation and relocation. Available in six standard sizes ranging from 3′ × 3′ × 90″ to 4′ × 5′ × 90″, Stor-More® Framed Welded Wire Tenant Storage Lockers can be configured to meet your unique needs.

A padlock hasp is included on all lockers for increased security

All hinges are welded for extra security

SINGLE-TIER

PART No.	W × D × H	WEIGHT
Starter Unit		
ST133-FW	3′ × 3′ × 90″	126 lbs.
ST134-FW	3′ × 4′ × 90″	146 lbs.
ST135-FW	3′ × 5′ × 90″	165 lbs.
ST143-FW	4′ × 3′ × 90″	118 lbs.
ST144-FW	4′ × 4′ × 90″	148 lbs.
ST145-FW	4′ × 5′ × 90″	174 lbs.
Add-On Unit		
AD133-FW	3′ × 3′ × 90″	94 lbs.
AD134-FW	3′ × 4′ × 90″	101 lbs.
AD135-FW	3′ × 5′ × 90″	113 lbs.
AD143-FW	4′ × 3′ × 90″	91 lbs.
AD144-FW	4′ × 4′ × 90″	107 lbs.
AD145-FW	4′ × 5′ × 90″	121 lbs.

DOUBLE-TIER

PART No.	W × D × H	WEIGHT
Starter Unit		
ST233-FW	3′ × 3′ × 90″	154 lbs.
ST234-FW	3′ × 4′ × 90″	182 lbs.
ST235-FW	3′ × 5′ × 90″	208 lbs.
ST243-FW	4′ × 3′ × 90″	166 lbs.
ST244-FW	4′ × 4′ × 90″	195 lbs.
ST245-FW	4′ × 5′ × 90″	222 lbs.
Add-On Unit		
AD233-FW	3′ × 3′ × 90″	122 lbs.
AD234-FW	3′ × 4′ × 90″	139 lbs.
AD235-FW	3′ × 5′ × 90″	156 lbs.
AD243-FW	4′ × 3′ × 90″	134 lbs.
AD244-FW	4′ × 4′ × 90″	151 lbs.
AD245-FW	4′ × 5′ × 90″	168 lbs.

TRIPLE-TIER

PART No.	W × D × H	WEIGHT
Starter Unit		
ST333-FW	3′ × 3′ × 90″	174 lbs.
ST334-FW	3′ × 4′ × 90″	207 lbs.
ST335-FW	3′ × 5′ × 90″	238 lbs.
ST343-FW	4′ × 3′ × 90″	186 lbs.
ST344-FW	4′ × 4′ × 90″	220 lbs.
ST345-FW	4′ × 5′ × 90″	252 lbs.
Add-On Unit		
AD333-FW	3′ × 3′ × 90″	142 lbs.
AD334-FW	3′ × 4′ × 90″	164 lbs.
AD335-FW	3′ × 5′ × 90″	186 lbs.
AD343-FW	4′ × 3′ × 90″	154 lbs.
AD344-FW	4′ × 4′ × 90″	176 lbs.
AD345-FW	4′ × 5′ × 90″	198 lbs.

OPTIONS

PART No.	W × D	WEIGHT
Locker Tops		
LT33-FW	3′ × 3′	6 lbs.
LT34-FW	3′ × 4′	6 lbs.
LT35-FW	3′ × 5′	8 lbs.
LT43-FW	4′ × 3′	6 lbs.
LT44-FW	4′ × 4′	8 lbs.
LT45-FW	4′ × 5′	8 lbs.
Locker Backs		
SMBK3690-FW	3′ × 90″	30 lbs.
SMBK4890-FW	4′ × 90″	40 lbs.
Bottom Shelf		
LS33	3′ × 3′	20 lbs.
LS34	3′ × 4′	25 lbs.
LS35	3′ × 5′	30 lbs.
LS43	4′ × 3′	20 lbs.
LS44	4′ × 4′	25 lbs.
LS45	4′ × 5′	30 lbs.

SINGLE-TIER COMPLETE
WITH TOP & BACK PANEL

PART No.	W × D × H	WEIGHT
Starter Unit		
ST133-FW-COM	3′ × 3′ × 90″	162 lbs.
ST134-FW-COM	3′ × 4′ × 90″	182 lbs.
ST135-FW-COM	3′ × 5′ × 90″	203 lbs.
ST143-FW-COM	4′ × 3′ × 90″	164 lbs.
ST144-FW-COM	4′ × 4′ × 90″	196 lbs.
ST145-FW-COM	4′ × 5′ × 90″	222 lbs.

DOUBLE-TIER COMPLETE
WITH TOP & BACK PANEL

PART No.	W × D × H	WEIGHT
Starter Unit		
ST233-FW-COM	3′ × 3′ × 90″	190 lbs.
ST234-FW-COM	3′ × 4′ × 90″	218 lbs.
ST235-FW-COM	3′ × 5′ × 90″	246 lbs.
ST243-FW-COM	4′ × 3′ × 90″	212 lbs.
ST244-FW-COM	4′ × 4′ × 90″	243 lbs.
ST245-FW-COM	4′ × 5′ × 90″	270 lbs.

TRIPLE-TIER COMPLETE
WITH TOP & BACK PANEL

PART No.	W × D × H	WEIGHT
Starter Unit		
ST333-FW-COM	3′ × 3′ × 90″	210 lbs.
ST334-FW-COM	3′ × 4′ × 90″	243 lbs.
ST335-FW-COM	3′ × 5′ × 90″	276 lbs.
ST343-FW-COM	4′ × 3′ × 90″	232 lbs.
ST344-FW-COM	4′ × 4′ × 90″	268 lbs.
ST345-FW-COM	4′ × 5′ × 90″	300 lbs.

SPECIFICATIONS

Panels / Doors	
Frame	14-gauge 1 ¼″ × 1 ¼″
Wire	10-gauge welded
Grid Opening	2″ × 2″
Hinge Type	Steel pin butt
Padlock Hasp	Yes (padlocks sold separately)
Shelves	
Solid	18-gauge galvanized sheet metal (only with double- and triple-tier)
Options	
Top (Mesh)	10-gauge welded wire, 2″ × 2″ grid opening
Bottom (Solid)	18-gauge galvanized sheet metal
Back (Mesh)	10-gauge welded wire, 2″ × 2″ grid opening
Back (Solid)	18-gauge galvanized sheet metal (back is required for back-to-back units)
General	
Finish	Powder Coated
Warranty	1 Year

CONFIGURATION INSTRUCTIONS

Modular design makes Stor-More® lockers easy to plan, install and relocate. Available in single-, double- and triple-tier units, and can be combined. Begin with starter unit, single-, double- or triple-tier and complete row with add-on units.

Single-row locker configurations installed against an existing wall do not require optional back panels. Double-row locker configurations share common back panels.

SINGLE TIER

Starter
1 single-tier door
2 end-run panels

Add-On
1 single-tier door
1 side panel

DOUBLE TIER

Starter
1 double-tier door
2 end-run panels
1 shelf

Add-On
1 double-tier door
2 side panels
1 shelf

TRIPLE TIER

Starter
1 triple-tier door
2 end-run panels
2 shelves

Add-On
1 triple-tier door
1 side panel
2 shelves

COMPLETE UNIT

Starter
1 triple-tier door
2 end-run panels
1 tip panel
1 back panel

Tier(s)
0–2 shelves
(specify)