

VERSA GUARD™ Machine guarding



THE MACHINE GUARDING SYSTEM THAT BLENDS FUNCTION, FLEXIBILITY AND COST-FRIENDLINESS

STURDY SYSTEM

With 90 degree bends at the top and bottom of all panels, the rigidity of this system is unparalleled compared with other frameless systems.

UNSURPASSED ADJUSTABILITY

Panels can easily be adapted before delivery or on-site, and it is easy to make cut-outs without any need for welding.

QUICK & EASY ASSEMBLY

All mounting hardware and floor anchors are included and posts are predrilled for expedited assembly.

EASILY COMBINED WITH OUR SAF-T-FENCE® SYSTEM

Can be used where risk of impact is low and seamlessly blended to our Saf-T-Fence[®] system in higher-risk sections.

Our Frameless Machine Guarding system is an attractive guarding solution that provides great visibility around any machine. Welded at each intersection in its tight $1\frac{1}{4} \times 2\frac{1}{2}$ grid pattern, this system can be installed as close to 8" to hazard (per ISO 13857). This allows you to install much closer than the conventional $2^{"} \times 2^{"}$ grid pattern, which cannot be installed closer than $33\frac{1}{2}$ ". With this extra $25\frac{1}{2}$ " in distance, you can more efficiently utilize your floor space.

With simple mounting clips, this frameless system is easily reconfigurable, flexible and installs 25% faster than substitutes by employing fewer parts and utilizing self-tapping screws.







Easy to install with clip and Tek screws

A 6" × 6" footplate is available for areas that need extra support



VERSA GUARD[™] Machine Guarding



PANELS

PART No.	WIDTH WEIGH				
35" Height					
V-13-MB	10"	4 lbs.			
V-23-MB	22″	7 lbs.			
V-33-MB	34″	10 lbs.			
V-43-MB	46″	13 lbs.			
V-53-MB	58″	16 lbs.			
V-63-MB	70″	19 lbs.			
V-83-MB	94″	26 lbs.			
V-103-MB	118″	32 lbs.			
47" Height					
V-14-MB	10″	4 lbs.			
V-24-MB	22″	8 lbs.			
V-34-MB	34″	12 lbs.			
V-44-MB	46″	16 lbs.			
V-54-MB	58″	21 lbs.			
V-64-MB	70″	25 lbs.			
V-84-MB	94″	33 lbs.			
V-104-MB	118″	41 lbs.			
59" Height					
V-15-MB	10"	5 lbs.			
V-25-MB	22″	10 lbs.			
V-35-MB	34″	15 lbs.			
V-45-MB	46″	20 lbs.			
V-55-MB	58″	26 lbs.			
V-65-MB	70″	31 lbs.			
V-85-MB	94" 41 lbs				
V-105-MB	118″ 51 lb				
Note					
For 5' High System	(1) 59" Hi				
For 6' High System	(2) 35" Hi	gh Panels			
For 7' High System	(1) 35" High Panel + (1) 47" High Panel				
For 8' High System	(2) 47" High Panels				

POSTS

PART No.	HEIGHT	WEIGHT
V-P5-SY	5′	10 lbs.
V-P6-SY	6'	11 lbs.
V-P7-SY	7'	13 lbs.
V-P8-SY	8'	15 lbs.

DOORS

	5' High		6' High		7' High		8' High	
WIDTH	PART No.	WEIGHT	PART No.	WEIGHT	PART No.	WEIGHT	PART No.	WEIGHT
Hinge Door								
3′	V-H35	25 lbs.	V-H36	34 lbs.	V-H37	34 lbs.	V-H38	64 lbs.
4'	V-H45	31 lbs.	V-H46	42 lbs.	V-H47	46 lbs.	V-H48	75 lbs.
Hinge Pair Door								
6′	V-HP65	45 lbs.	V-HP66	82 lbs.	V-HP67	70 lbs.	V-HP68	160 lbs.
8′	V-HP85	50 lbs.	V-HP86	100 lbs.	V-HP87	94 lbs.	V-HP88	190 lbs.
Slide Do	or*							
3′	Consult	factory	Consult factory		V-S37	34 lbs.	V-S38	88 lbs.
4'	Consult	factory	Consult factory		V-S47	46 lbs.	V-S48	100 lbs.
5′	Consult	factory	Consult factory		V-S57	58 lbs.	V-S58	132 lbs.
6′	Consult	factory	Consult factory		V-S67	70 lbs.	V-S68	143 lbs.
8'	Consult	factory	Consult factory		V-S87	94 lbs.	V-S88	170 lbs.
10'	Consult	factory	Consult factory		V-S107	106 lbs.	V-S108	249 lbs.
Slide Pa	ir Door*							
8'	Consult	factory	Consult	factory	V-SP87	70 lbs.	V-SP88	236 lbs.
10'	Consult	factory	Consult	factory	V-SP107	94 lbs.	V-SP108	265 lbs.
Clear Ac	cess Slide	Door*						
6′	V-SC65	110 lbs.	V-SC66	130 lbs.	V-SC67	165 lbs.	-	-
Clear Ac	Clear Access Slide Pair Door*							
8'	V-SPC85	125 lbs.	V-SPC86	165 lbs.	V-SPC87	245 lbs.	-	-
12'	V-SPC125	155 lbs.	V-SPC126	205 lbs.	V-SPC127	300 lbs.	-	-

*Note: Actual sliding door exceeds opening width. Please consult factory for exact dimension.

LOCKING OPTIONS

	Door Type					
	Н	HP	S	SP	CS	CSP
Snap Lock	\checkmark	\checkmark	\checkmark	\checkmark	\checkmark	\checkmark
Cylinder Lock (Key Lock Not Included)	\checkmark	\checkmark	\checkmark	\checkmark	\checkmark	\checkmark
Keyed Alike Cylinders	\checkmark	\checkmark	\checkmark	\checkmark	\checkmark	\checkmark
Keyed Different Cylinders	\checkmark	\checkmark	\checkmark	\checkmark	\checkmark	\checkmark
Safety Switch with Slide Bolt Actuator	\checkmark	\checkmark	\checkmark	\checkmark	\checkmark	\checkmark
Locking Safety Switch with Slide Bolt Actuator	\checkmark	\checkmark	\checkmark	\checkmark	\checkmark	\checkmark

SPECIFICATIONS		
Panels		
Wire	8-gauge welded	
Grid Opening	1 ¼"×2½"	
Posts		
Tube	2"×2", 14-gauge	
Foot Plate	6"×2"×¼"	
Doors		
Wire	10-gauge welded	
Grid Opening	1¼"×2½"	
General		
Finish	Powder Coated	
Warranty	1 Year	







Cylinder Lock



Safety Switch (Multiple Options Available)