



5" Rebounding Steel Bollard

PROTECTIVE GUARDING - SLOWSTOP®

SPEC SHEET | P/N **SS5Y-42-RB**



Product Specifications

| | |
|--------------------|--|
| Color | RAL 1023 Yellow Pipe on RAL 9005 Black Pedestal |
| Diameter | 5.56" (5" ANSI Schedule 40) |
| Product Weight | 110 lb. |
| Product Height | 42" overall |
| Impact Rating | I12-5 (13,600 joules) |
| Temperature Rating | -40°F - 150°F |
| Pipe Coating | 60 µm Galvanized + 150 µm Polyester Outdoor Powder Coating |
| Cast-Iron Coating | Environmentally Friendly Water-based E-Coat + Polyester Outdoor Powder Coating |
| Set Screws | Six (6) M16 |
| Anchor Screws | Six (6) 5/8" x 5-1/2" Concrete |
| Cap | Metal, RAL 1023 Yellow |

Recommended Uses

| |
|--|
| Medium to heavy duty |
| Where forks or cantilevers typically shear bolts |
| Interior dock doors, corners, rollup doors, fire risers, & internal access doors |
| Exterior signpost |
| Equipment and storage rack guarding |
| Pedestrian safety |
| Access denial |
| Utility protection |
| Pre- and post-tensioned concrete capable |
| Internal use where forks have speed |
| Not for K-Rated security use |

Impact Chart

| | |
|-------------------|--------------------|
| Impact Angle | 90° |
| Rating | 13,600 joules |
| ANSI MH 31.2 | I12-5 |
| Mass (lbs) | Speed (mph) |
| 5,000 | 7.7 |
| 7,500 | 6.3 |
| 10,000 | 5.5 |
| 12,500 | 4.9 |
| 15,000 | 4.5 |
| 17,500 | 4.1 |
| 20,000 | 3.9 |
| 25,000 | 3.5 |
| 30,000 | 3.2 |

4955 Stout Drive, San Antonio, TX 78219
 (210) 736-4477 | 1-800-736-5256 | info@impactrecovery.com
impactrecovery.com
 January 2024

